



INN°VATIVE SOLUTION





NEXT STARTS

For 100 years, Rheem has been a leader in product innovation.

And the best part is we're just getting started. Now, as we celebrate all that we've accomplished together, we look towards the future of air and water. To what's next. To remaining true to our values, while working with our customers to create a globally connected and forward-looking vision.

Our journey began in 1925, as a small family business based in Arkansas, USA. Since then, we have evolved into a global symbol of trust and quality within the industry. Establishing a robust presence in the Middle East as far back as the 1980s, Rheem has consistently introduced world-leading product innovations for both commercial and residential projects. From our manufacturing facilities in Dubai, to our Innovation and Learning Centers (ILCs) across the United Arab Emirates and Kingdom of Saudi Arabia, Rheem is dedicated to designing, building and supplying the most reliable, environmentally responsible and technologically advanced products in the industry. And, whilst we always want to stay one step ahead, we will always stay true to our core values. We are committed to making a difference with the products we create, for the people we serve and for the planet we call home.





HISTORY



1889

Edwin Ruud invents the first gas storage water heater.



1925

Brothers Richard and Donald Rheem establish Rheem Manufacturing Company.



1930-50

Automatic gas storage water heaters are produced under the Ruud business. Rheem enters the HVAC business, advertising central heating and air conditioning systems.



2025

Rheem celebrates 100 years of innovation.



2024

The largest Rheem Innovation Learning Center opens in Saudi Arabia.



2021

Rheem opens a new air conditioning factory in UAE.



1970

Air conditioning headquarters open in Fort Smith, Arkansas. Water heating headquarters are established in Montgomery, Alabama.



1980-90

- Paloma Co. Ltd of Nagoya, Japan, acquires Rheem.
- The Richmond brand for water heating is created.
- Nuevo Laredo (WHD) opens.



2000-08

- Rheem pioneers the first gas storage water heater, originally patented by Edwin Ruud in 1890.
- Nuevo Laredo (ACD) opens.
- Rheem's headquarters open in Atlanta.



2020

Rheem opens an Innovation and Learning Center in UAE.



2012

Rheem Manufacturing MEA FZE (Dubai office) is established.



2009-10

- Rheem introduces tankless water heaters.
- Research & Development (R&D) lab opens in Mexico.

OUR C^oMMITMENT TO SUSTAINABILITY.

At Rheem, we are committed to developing products which consume fewer resources, generate less waste and ensure simpler, safer processes.

These solutions are designed to dramatically cut our impact on the environment, whilst empowering both our customers and employees to work and live sustainably.



DEGREES OF INNOVATION

Our 2025 Goal: Launch a line of heating, cooling and water heating products that boast a 50% reduction in greenhouse gas footprint.



DEGREES OF EFFICIENCY

Our 2025 Goal: Reduce greenhouse gas emissions by 50% and achieve Zero Waste to Landfill in our global manufacturing operations.



DEGREES OF LEADERSHIP

Our 2025 Goal: Train 250,000 plumbers, contractors, and key influencers on sustainable products or sustainable installation and recycling best practices.









VRF WATER HEATER HEAT RECOVERY SYSTEM FEATURES





CONTINUOUS HOT WATER PRODUCTION WHILE COOLING THE SPACE



ENERGY SAVINGS UPTO 84%



HIGH EFFICIENCY



CONTINUOUS HOT WATER UPTO 70 DEG C




ADVANCED RHEEMSMART CONTROLS WITH MULTIPLE MODES



LOWER NOISE LEVEL

HOW IT WORKS?

The heat absorbed by VRF indoor units is used to heat the water. The heated refrigerant exchanges heat with cold water in the SMARTLINK heat exchanger.



OPERATION IN COOLING/HEATING MODE





MODES OF OPERATION

Standard Efficiency

- VRF will work up to 45 °C water temperature
- VRF & Electrical Heater will both work from 45 °C to 55 °C water temperature
- Above 55 °C only Electrical Heater will work

High Efficiency

- VRF is prioritized & used to heat water majority of the time
- Hot water temperature up to 55 °C is by VRF only
- Time taken to heat the water is relatively higher


Quick Heating


VRF and Electrical Heater both will work from start




OPERATION MODES LOGIC

Below showcases the operation modes logic of the system.










HIGH ENERGY SAVINGS

Based on the real time testing and simulations which VRF Water Heater Heat Recovery System is used, up to 84% savings can be achieved in comparison to conventional electric water heater.





MODES COMPARISON

Below shows the comparison between Standard Efficiency and High Efficiency modes at same condition of 40 °C ambient, for 10hp VRF unit operating at 100% load.





105 Min Heating Time



CONTINUOUS HOT WATER PRODUCTION WHILE COOLING THE SPACE

The VRF Water Heater Heat Recovery System is a product of Rheem's continuous expertise in both Air Conditioning and Water Heating fields.

The system is capable of producing hot water up to 55 degrees Celsius by Heat Recovery from VRF while the VRF is cooling the space.



MULTIPLE APPLICATION SOLUTION







Residential Complex



Office



Restaurant



Staff Accommodation



Clinic/Hospital



Gym



Hotel



School/University

HIGH WATER TEMPERATURE PRODUCTION

The system is capable to heat the water up to 70 °C which minimizes the growth of bacteria inside the tank.



LOW NOISE LEVELS

Since some of the refrigerant heat is exchanged with the water, the condenser fan will operate at lower speed to cool down the refrigerant which in return results in lower noise levels.





VRF SPECIFICATIONS

		Model	SAVR-H250/XR1MC-HW	SAVR-H280/XR1MC-HW	SAVR-H330/XR1MC-HW
	Power Supply	V~,Hz,Ph	380~415V,3N,50/60Hz	380~415V,3N,50/60Hz	380~415V,3N,50/60Hz
	Cooling (T1)	kW	25.2	28.2	33.3
		TR	7.2	8.06	9.51
		Btu/h	86000	96000	114000
		kW	22.2	24.9	30.6
Capacity	Cooling (T3)	TR	6.34	7.11	8.74
		Btu/h	76000	85000	104000
	Heating (H1)	kW	25.2	28.2	33.3
		TR	7.2	8.06	9.51
		Btu/h	86000	96000	114000
	Rated Cooling Power Input (T1)	kW	5.73	6.78	8.14
	Rated Cooling Current (T1)	А	9.04	10.94	13.11
Electric Data	Rated Cooling Power Input (T3)	kW	6.2	7.87	9.29
LICCITIC Data	Rated Cooling Current (T3)	А	10	12.69	14.98
	Rated Heating Power Input (T1)	kW	5.55	6.29	7.67
	Rated Heating Current (T1)	А	8.75	10.13	12.37
	EER(T1)	W/W	4.4	4.15	4.1
		Btu/(h*W)	15	14.15	14
Performance	EER(T3)	W/W	3.59	3.17	3.28
	EEN(13)	Btu/(h*W)	12.25	10.8	11.2
	COP(H1)	W/W	4.54	4.48	4.34
CSPF		Btu/h/W	16.5	15.5	15
MCA /Max. Current		А	20.2	21.1	24.4
Outdoor Fan	Туре		Axial	Axial	Axial
	Fan Quantity		1	1	2
Air Flow Volume		CFM	7059	7059	8235
7 til 1 low volume		m3/h	12000	12000	14000
Noise Level		dB(A)	45-58	45-58	45-61
Dimension(W×D×H)	Net	mm	990×765×1635	990×765×1635	1340×765×1635
	Packing	mm	1030×825×1865	1030×825×1865	1395×815×1865
Weight	Net	kg	225	225	257
	Gross	kg	235	235	272
	Туре		R410A	R410A	R410A
Refrigerant type/ Quantity	Charged Volume	g	14000	14000	14000
	AC Liquid Side	mm	12.7	12.7	15.9
	AC Gas Side	mm	22.2	22.2	28.6
Refrigerant Pipe	Water Liquid Side	mm	9.52	9.52	9.52
	Water Gas Side	mm	15.88	15.88	15.88
	Max. Length	m	1000	1000	1000
	Max. Height	m	110/130	110/130	110/130
Ambient Temp (Cooling/Heating)		℃	-10~55/-20~24	-10~55/-20~24	-10~55/-20~24

Note: X in the model number denotes below:

X = 5, 50 HzX = 6, 60 Hz

VRF SPECIFICATIONS

		Model	SAVR-H400/XR1MC-HW	SAVR-H450/XR1MC-HW
	Power Supply	V~,Hz,Ph	380~415V,3N,50/60Hz	380~415V,3N,50/60Hz
	,	kW	40.0	45
	Cooling (T1)	TR	11.43	12.86
		Btu/h	136000	154000
		kW	35.7	39
Capacity		TR	10.2	11.14
	Cooling (T3)	Btu/h	122000	133000
		kW	40	45
	Heating (H1)	TR	11.43	12.86
		Btu/h	136000	154000
	Rated Cooling Power Input (T1)	kW	9.41	11
	Rated Cooling Current (T1)	A	380~415V,3N,50/60Hz 40.0 11.43 136000 35.7 10.2 122000 40 11.43 136000	17.73
 Electric Data	Rated Cooling Power Input (T3)	kW		13.93
Licetife Data	Rated Cooling Current (T3)	А		22.45
	Rated Heating Power Input (T1)	kW	8.86	10.48
	Rated Heating Current (T1)	А	11.43 136000 35.7 10.2 122000 40 11.43 136000 9.41 15.17 11.96 19.28 8.86 14.28 4.24 14.45 2.99 10.2 4.5 14.2 39.3 Axial 2 9412 16000 45-61 1340×765×1635 1395×815×1865 314 329 R410A 16000 15.9	16.89
	EER (T1)	W/W	4.24	4.1
		Btu/(h*W)	14.45	14
 Performance	EER (T3)	W/W	2.99	2.8
		Btu/(h*W)	10.2	9.55
	COP (H1)	W/W	4.5	4.31
CSPF		Btu/h/W	14.2	14
MCA /Max. Current		А	39.3	40.6
Outdoor For	Туре		Axial	Axial
Outdoor Fan	Fan Quantity		40.0 11.43 136000 35.7 10.2 122000 40 11.43 136000 9.41 15.17 11.96 19.28 8.86 14.28 4.24 14.45 2.99 10.2 4.5 14.2 39.3 Axial 2 9412 16000 45-61 1340×765×1635 1395×815×1865 314 329 R410A 16000 15.9 28.6 9.52 15.88 1000 110/130	2
Air Flow Volume		CFM	380~415V,3N,50/60Hz 40.0 11.43 136000 35.7 10.2 122000 40 11.43 136000 9.41 15.17 11.96 19.28 8.86 14.28 4.24 14.45 2.99 10.2 4.5 14.2 39.3 Axial 2 9412 16000 45-61 1340×765×1635 1395×815×1865 314 329 R410A 16000 15.9 28.6 9.52 15.88 1000 110/130	9412
All Flow Volume		m3/h		16000
Noise Level		dB(A)	45-61	45-61
Dimension (W×D×H)	Net	mm	1340×765×1635	1340×765×1635
	Packing	mm	4.5 14.2 39.3 Axial 2 9412 16000 45-61 1340×765×1635 1395×815×1865 314	1395×815×1865
Weight	Net	kg	136000 35.7 10.2 122000 40 11.43 136000 9.41 15.17 11.96 19.28 8.86 14.28 4.24 14.45 2.99 10.2 4.5 14.2 39.3 Axial 2 9412 16000 45-61 1340×765×1635 1395×815×1865 314 329 R410A 16000 15.9 28.6 9.52 15.88 1000 110/130	314
Weignt	Gross	kg	329	329
	Туре		R410A	R410A
 Refrigerant type/ Quantity	Charged Volume	g	16000	16000
Herrigerant type/ Quantity	AC Liquid Side	mm	15.9	15.9
	AC Gas Side	mm	28.6	28.6
	Water Liquid Side	mm	9.52	9.52
Refrigerant Pipe	Water Gas Side	mm	15.88	15.88
	Max. Length	m	1000	1000
	Max. Height	m	110/130	110/130
Ambient Tem	p (Cooling/Heating)	℃	-10~56/-20~24	-10~55/-20~24

Note: X in the model number denotes below:

X = 5, 50 HzX = 6, 60 Hz

TANK SPECIFICATIONS

	Model	Units	RHC 300 - 500
	Capacity	L	300 - 500
	Capacity of the back-up heater	kW	3 - 3, 5
CALORIFIER DETAILS	Calorifier material		Glasslined Steel / SS316 L
	Max pressure	bar	8 / 10 bar
	Outer cover		Aluminum
	Temp range	С	25-70
	Dimension (W*H*D)	mm	332.5*121*87.4
	Heat exchange area	m³	2.794
	Rated water temp Range	℃	-20~110
CAMA DEL INIVIDEE A III C	Piping connections	inch	R1"
SMARTLINK DETAILS	Safety valve set pressure	Мра	0.3
	Flow switch	m³/h	0.6
	Drainage pipe connection	mm	φ25
	Expansion tank	L	8
	Protection class	/	IP44
	Rated prower	Hz	230-50/60
	Туре	/	canned pump
	Power input	W	4~95
PRIMARY PUMP (INBUILT)	current	A	0.04~0.75
	Max Rotating speed	r/min	4500
	Insulation class	/	class F
	Pump head	m	9
	Pump Flow	m³/h	4.5
	Liquid Side	mm	15.88
Refrigerant Pipe	Gas Side	mm	9.52
	Drainage	mm	DN25



engineered for life™













@rheemmea

www.rheem-mea.com

Rheem Middle East