



The new degree of comfort.™

Point-of-use electric water heaters feature a space-saving design for installation in limited spaces

Longer Life

- Rheem Exclusive Magnesium anode rod provides long-lasting tank protection

Features

- High efficiency heating element
- Over-temperature protector cuts off power in excess temperature situations
- Automatic thermostat keeps water at desired temperature
- Wall mount kits available for easy installation
- Exclusive Rheemglas tank lining resists corrosion
- ASME rated temperature and pressure relief valve
- R-Foam Cyclopentane insulation for superior heat retention
- Maximum tank working pressure of 150 PSI (10 BARS)
- Factory tested @ 300 PSI

Plus...

- These units are UL listed and comply with Underwriter's Laboratories Specifications 174 and IEC 60335-2-21



POINT-OF-USE

23, 38, 57, 76 & 114-Liter Capacities
 220, 230 & 240 Volt AC/Single Phase
 50 Hz / 60 Hz
 2-Wire Single Phase Electric

. Available in Simultaneous and Non-Simultaneous heating elements




MODEL NO.	WATTAGE @230 / 400 V
85VP6	1500 & 2000
85VP10	1500, 2000 & 3000
85VP15	1500, 2000, 3000 & 4500
85VP20	2000, 2500, 3000, 3500 & 4500
85VP30	2000, 3000, 4500 & 6000

DESCRIPTION		TESTING	ROUGHING IN DIMENSIONS (SHOWN IN INCHES)					APPROX. SHIP. WT (LBS)
GAL. CAP.	MODEL NUMBER		HEIGHT(B)	HEIGHT TO HOT WATER OUTLET (C)	DIAMETER(A)	HEIGHT TO SIDE T&P VALVE(D)	HEIGHT TO Cold water inlet(E)	
6	85VP6-1	UL / IEC	15-1/4	12-1/2	15-3/4	11-1/2	4-1/4	36
10	85VP10	UL / IEC	23	20-1/2	15-3/4	19-1/2	4-1/4	46
15	85VP15	UL / IEC	24-1/5	22	17-3/4	21	4-1/2	54
20	85VP20	UL / IEC	25-1/4	22-3/4	19-3/4	21-3/4	5	69
30	85VP30	UL / IEC	30	23	21-3/4	23	2 3/04	91

• 6 through 30 gallon models: 3/4" N.P.T. outlet, inlet, anode rod. T&P valve connections. Not available with 3 phase wiring. Water heaters furnished standard with 230volt AC,2000 watt single element.

Special wiring options – a limited number of wiring options are available. Consult factory for price and availability.

CONSTRUCTION DETAILS: The cold water enters the tank a few inches from the bottom. Both hot and cold water lines may be connected directly to the water heater without special nipples or tees. The relief valve simply screws into the opening provided.



Energy Factor and Average Annual Operating Costs based on D.O.E.(Department of Energy) test procedures

**Recovery = wattage / 2.42 x temp. rise °F.
 Example: 4500W = 21 GPH
 2.42 x 90°

In keeping with its policy of continuous progress and product improvement, Rheem reserves the right to make changes without notice.

RMEA Manufacturing LLC.
 The Greens - Dubai, UAE
 www.rheem-mea.com



INTEGRATED HOME COMFORT