



The new degree of comfort.™

RH-EVS/R-SS Large Volume Stainless Steel Series are available in 200 to 2500-gallon storage capacities Vertical round & square models

Standard features

- Stainless steel tank (AISI 304L quality)
- Incoloy 825 heating elements
- Electrostatic powder paint coated galvanized steel outer jacket
- Immersed type regulating thermostat
- Manual reset high limit thermostat
- Electrical control cabinet with full length hinged doors with key lock
- Magnetic Contactors
- All models are equipped with UL listed terminal blocks for simplicity of installation
- Factory installed ASME temperature and pressure relief valve
- 180° F (82° C) temperature operation
- 125 PSI (8.6 bar) working pressure
- Heater steps on/off switches with pilot lamps
- Factory installed temperature gauge
- Factory installed pressure gauge
- Magnesium Anode rods to ensure long life and corrosion resistance
- Electrostatic powder paint coated galvanized steel control cabinet with special polyurethane gasket
- Special wrench for heating elements is provided
- Factory installed full-flow, brass drain valve for faster draining
- Hand-hole sediment cleanout (500 Liter and Larger models)
- Optional features includes
 - .Non UL heaters.
 - .LCD digital temp. display
 - .Main disconnect switch.

Optional features

- AISI 316L quality stainless steel tank material
- Hot dipped galvanized steel tank material (only on 4000-liter or greater capacities)
- Low water cut-off
- Lifting lugs
- Safety door interlock
- Man Way DN400 for 250-gallon (945-liter) and larger models
- Stainless steel (AISI 304 or 316) outer jacket
- Stainless steel (AISI 304 or 316) control cabinet
- 150 PSI (10.34 bar) working pressure
- Proportional Solid State Controller
- Factory installed full-flow, brass drain valve for faster draining
- Electronic Multi Stage Controller with LCD Display
- Water Pressure reducing valve
- 24 Hrs. or 7 Days Clock
- Audible Alarm and Silencer



Rheem EVS/R-SS series

200-Gallon to 2500-Gallon
Capacities
ASME Construction Option
3-Year Limited Warranty



Safety and Construction

- These products are design certified by Underwriters Laboratories (UL) to meet UL standard 1453. Also Non-UL unit configuration is available as option.

- ASME construction in accordance with the requirements of ASME Boiler and Pressure Vessel Code Section IV Part HLW

Warranty

- 3-year limited tank warranty
- 1-year limited parts warranty

In keeping with its policy of continuous progress and product improvement, Rheem reserves the right to make changes without notice.






The new degree of comfort.™



Large Storage Commercial
Stainless Steel Electric
Water Heaters



Vertical Round Models

MODEL NUMBER	GALLON CAPACITY	MAX KW	DIMENSIONS			WATER CONNECTION	
			A (MM)	B (MM)	C MAX.* (MM)	INLET	OUTLET
RH-EVR-SS-200	200	60	1980	830	1220	1-1/4"	1-1/4"
RH-EVR-SS-250	250	135	1885	980	1370	1-1/4"	1-1/4"
RH-EVR-SS-300	300	150	2188	980	1370	1-1/4"	1-1/4"
RH-EVR-SS-400	400	195	2036	1200	1590	1-1/2"	1-1/2"
RH-EVR-SS-500	500	195	2145	1300	1690	1-1/2"	1-1/2"
RH-EVR-SS-600	600	216	2485	1300	1690	1-1/2"	1-1/2"
RH-EVR-SS-700	700	216	2549	1300	1600	2"	2"
RH-EVR-SS-800	800	216	2629	1450	1900	2"	2"
RH-EVR-SS-1000	1000	360	2248	1800	2250	2-1/2"	2-1/2"
RH-EVR-SS-1200	1200	450	2588	1800	2250	2-1/2"	2-1/2"

- Control panel dimensions differ according to KW rating. Dimension C is given as per max. KW

In keeping with its policy of continuous progress and product improvement, Rheem reserves the right to make changes without notice.

Rheem Manufacturing MEA FZE

Dubai Airport Free Zone - Dubai, UAE

www.rheem-mea.com




INTEGRATED HOME COMFORT



The new degree of comfort.™

Water | Large Storage Commercial
Stainless Steel Electric
Water Heaters



Vertical Square Models

MODEL NUMBER	GALLON CAPACITY	MAX KW	DIMENSIONS			
			A (MM)	B (MM)	B+D MAX.* (MM)	WATER CONNECTION
INLET	OUTLET					
RH-EVS-SS-1000	1000	360	2749	1700	2150	2-1/2" 2-1/2"
RH-EVS-SS-1200	1200	450	2646	1900	2350	2-1/2" 2-1/2"
RH-EVS-SS-1300	1300	450	2815	1900	2350	2-1/2" 2-1/2"
RH-EVS-SS-1400	1400	450	2985	1900	2350	2-1/2" 2-1/2"
RH-EVS-SS-1500	1500	450	3164	1900	2350	3" 3"
RH-EVS-SS-1600	1600	450	2785	2100	2550	3" 3"
RH-EVS-SS-1800	1800	540	3106	2100	2550	3" 3"
RH-EVS-SS-2000	2000	540	3288	2100	2550	3" 3"
RH-EVS-SS-2250	2250	612	3719	2100	2550	4" 4"
RH-EVS-SS-2500	2500	800	4059	2100	2550	4" 4"

• Control panel dimensions differ according to KW rating. Dimension B+D is given as per max. KW

In keeping with its policy of continuous progress and product improvement, Rheem reserves the right to make changes without notice.

Rheem Manufacturing MEA FZE
Dubai Airport Free Zone - Dubai, UAE
www.rheem-mea.com



INTEGRATED HOME COMFORT