Vertical and horizontal point-of-use water heaters with shorter heating time and factory installed heavy duty moutning brackets

Performance

- •FHR: 50 105 liters, based on liter capacity
- •Recovery rate is 35 Liters at a 32 degree Celsius rise

Longer Life

Magnesium anode rod that ensures long tank life

Features

- Durable copper heating element easy for replacement
- An integral over-temperature safety device and a childproof automatic thermostat are featured on all models
- Degree Of Protection IPX4
- Space saving design for installation in limited spaces
- Installed easily in replacement and new construction applications
- Factory installed heavy duty wall mounting bracket(s) included
- Exclusive Rheemglas tank lining resists corrosion

- Standard pressure relief valve for tank Safety
- Proprietary Class 1 Polyurethane Foam insulation process for superior heat retention
- Maximum tank working pressure of 125 PSI (8.5 BARS)
- All water connections are 1/2"NPT

Warranty

• 5-Year limited tank and 1 year parts warranty


MODEL	FULL CAPACITY HEATING TIME (+45°C)							
RH-MFG050	120 MINUTES							
RH-MFG080	150 MINUTES							
RH-MFG100	190 MINUTES							



Point-of-Use

30, 50, 80 & 100-Liter Capacities 230 Volt AC/ Single Phase 50 Hz / 60 Hz 2-Wire Single Phase Electric






10 11 12 13 16 Spacer Tub (Blue) Outer Upper Cover Inner Upper Dome Outer Hanging ½" Pipes 17 20 21 23 25 26 29 32 Electrical Cover Indicated Lamp 5 Nut's M6*1.25 Flange Tank Thermometer Frame


In keeping with its policy of continuous progress and product improvement, Rheem reserves the right to make changes without notice.


VERTICAL TYPE - WALL MOUNTED



MODEL	STORAGE CAPACITY		VOLTAGE	POWER	PACKING	SHIPPING WEIGHT		Α	В	С	D	Е	F
	LIT.	GAL.	(V)	(W)	DIMENSIONS (MM)	LBS	KG	(MM)	(MM)	(MM)	(MM)	(MM)	(MM)
RH-FMR030-VF	30	8	230	1500	410 x 386 x 532	23	11	370	475	189	100	240	113
RH-FMG050-VF	50	13	230	1500	490 x 480 x 590	33	17	450	496	190	100	240	136
RH-FMG080-VF	80	21	230	2000	490 x 480 x 802	44	23	450	700	190	100	240	136
RH-FMG100-VF	100	26	230	2000	490 x 480 x 947	55	26	846	846	190	100	240	136

HORIZONTAL TYPE - WALL MOUNTED







MODEL	STORAGE CAPACITY		VOLTAGE	POWER	PACKING	SHIPPING WEIGHT		Α	В	С	D	Е	F
	LIT.	GAL.	(V)	(W)	DIMENSIONS (MM)	LBS	KG	(MM)	(MM)	(MM)	(MM)	(MM)	(MM)
RH-FMG050-HF	50	13	230	1500	490 x 480 x 603	33	17	541	450	100	145	237	240
RH-FMG080-HF	80	21	230	2000	490 x 480 x 837	44	23	766	450	100	370	237	240
RH-FMG100-HF	100	26	230	2000	490 x 480 x 984	55	26	914	450	100	517	237	240

In keeping with its policy of continuous progress and product improvement, Rheem reserves the right to make changes without notice.